



	m/t	SR / DR												Potain GTMR 366				
		15	17	19	21	23	25	27	29	31	33	35	37	38	40	42	45	
8 - 11,7M	5,78	4,92	4,26	3,74	3,32	2,98	2,69	2,44	2,23	2,05	1,88	1,74	1,68	1,55	1,44	1,3		
8 - 13 M	6,65	5,67	4,93	4,34	3,86	3,47	3,14	2,86	2,62	2,41	2,23	2,06	1,99	1,85				
8 - 14,2M	7,48	6,39	5,56	4,9	4,37	3,94	3,57	3,26	2,99	2,76	2,55							
8 - 15,3M	8	6,99	6,09	5,38	4,8	4,33	3,93	3,59	3,3									

Technische Daten						
Heben	33PC20	2 drahtig		4 drahtig		
1. Schnelligkeit		5,4 m/min.	4000 kg	2,7 m/min.	8000 kg	
2. Schnelligkeit		30 m/min.	4000 kg	15 m/min.	8000 kg	
3. Schnelligkeit		60 m/min.	2000 kg	30 m/min.	4000 kg	
Laufkatze		15 - 30 - 58 m/min.				
Schwenken		0 - 0,8 omw./min.				
Kranfahren		max. 25 m/min.				
Druck auf Bodenfläche		0,85 kg./cm2				
Strom / Spannung		63	Ampere	380	V	
Strom / Spannung		100	KVA			